

Standard Flexible Couplings



Fernco's specially formulated PVC compound positively seals most sewer and drain connections.

Fernco makes the most complete line of couplings in the industry, from sizes 3/4" and larger. Custom large diameter couplings are available, along with shielded transitional couplings to ensure all pipes, underground and above-ground, can be connected with a Fernco coupling. Because Fernco couplings have earned a reputation for superior performance, you can have full confidence in their quality and reliability.

Tested designs backed by over five decades of proven experience

Available from 3/4" and larger

- Seals against infiltration and exfiltration
- Leak-proof, root-proof and resistant to many chemicals, ultra violet rays, fungus growth and normal sewer gas
- Conforms to ASTM D 5926, C 1173 and CSA B602
- Connects pipes of same or different materials and sizes
- Corrosion-resistant and rust-proof stainless steel clamps
- Made of elastomeric polyvinyl chloride (PVC)
- 4.3 PSI maximum test pressure
- 140°F maximum intermittent operating temperature
- 120°F maximum consistent operating temperature



Flexible Couplings

High Torque Clamps

STANDARD on all 18" and larger couplings



see sizes on pg. 17-24

1056 Series Couplings

Cl, Plastic, Copper, Steel or Lead to
Cl, Plastic, Copper, Steel or Lead

* Insert bushing included **Red** high torque clamps included new

6" x 6" (150 mm x 150 mm)	6.60 x 6.60 1056-66	6.60 x 6.60 1056-66RC	6.60 x 6.60 5056-66RC	
8" x 4" (200 mm x 150 mm)	8.51 x 4.38 1056-84*	8.64 x 4.50 1056-84RC*		8.64 x 4.38 1056-84EB
8" x 6" (200 mm x 150 mm)	8.51 x 6.38 1056-86	8.64 x 6.38 1056-86RC*	8.64 x 6.38 5056-86RC	8.64 x 6.38 1056-86EB
8" x 8" (200 mm x 200 mm)	8.64 x 8.64 1056-88	8.64 x 8.64 1056-88RC	8.64 x 8.64 5056-88RC	
10" x 8" (250 mm x 200 mm)	10.25 x 8.42 1056-10-8	10.63 x 8.62 1056-10-8RC	10.63 x 8.62 5056-10-8RC	10.63 x 8.38 1056-10-8EB
10" x 10" (250 mm x 250 mm)	10.63 x 10.63 1056-1010	10.63 x 10.63 1056-1010RC	10.63 x 10.63 5056-1010RC	
12" x 10" (300 mm x 250 mm)	12.50 x 10.65 1056-1210	12.52 x 10.75 1056-1210RC	12.52 x 10.75 5056-1210RC	12.52 x 10.60 1056-1210EB*
12" x 12" (300 mm x 300 mm)	12.52 x 12.52 1056-1212	12.52 x 12.52 1056-1212RC	12.52 x 12.52 5056-1212RC	
15" x 10" (375 mm x 250 mm)	15.44 x 10.60 1056-1510			15.44 x 10.60 1056-1510EB
15" x 12" (375 mm x 300 mm)	15.75 x 12.25 1056-1512	15.12 x 12.60 1056-1512RC		15.44 x 12.60 1056-1512EB
15" x 15" (375 mm x 375 mm)	15.44 x 15.44 1056-1515	15.92 x 15.92 1056-1515RC	15.92 x 15.92 5056-1515RC	
18" x 18" (450 mm x 450 mm)	19.00 x 19.00 1056-1818	19.10 x 19.00 1056-1818RC	19.10 x 19.10 5056-1818RC	
21" x 21" (525 mm x 525 mm)	22.50 x 22.50 1056-2121	22.50 x 22.50 1056-2121RC		
24" x 24" (600 mm x 600 mm)	26.61 x 10.00 1056-2424	25.10 x 25.10 1056-2424RC	25.10 x 25.10 5056-2424RC	
27" x 27" (700 mm x 700 mm)	28.30 x 28.30 1056-2727	28.30 x 28.30 1056-2727RC		

1057 Series Couplings

Concrete to DI

NOMINAL PIPE DIAMETER	STANDARD	STRONG BACK 1000 RC SERIES	STRONG BACK 5000 RC SERIES	ECCENTRIC
4" x 4" (100 mm x 100 mm)	5.51 x 5.00 1057-44*	5.51 x 5.00 1057-44RC*		
6" x 4" (150 mm x 100 mm)	7.58 x 5.00 1057-64*			7.58 x 5.00 1057-64EB*
6" x 6" (150 mm x 150 mm)	7.58 x 6.80 1057-66*	7.58 x 6.80 1057-66RC*		
6" x 8" (150 mm x 200 mm)	9.04 x 7.80 1057-68*	9.04 x 7.80 1057-68RC*		9.04 x 7.80 1057-68EB*
8" x 6" (200 mm x 150 mm)	10.00 x 6.80 1057-86*	10.00 x 6.80 1057-86RC*		
8" x 8" (200 mm x 200 mm)	10.00 x 8.92 1057-88	10.00 x 8.92 1057-88RC		
10" x 10" (250 mm x 250 mm)	12.40 x 11.12 1057-1010*	12.40 x 11.12 1057-1010RC*		
10" x 10" LC (250 mm x 250 mm)			14.00 x 11.12 5057-1010LCRC*	
12" x 6" (300 mm x 150 mm)	15.25 x 6.80 1057-12-6*			15.25 x 6.80 1057-12-6EB*