



### Under-Mount Apron-Front Kitchen Sink K-6487

### **Features**

- 30-inch minimum base cabinet width.
- Single bowl.
- 9-inch depth.
- Tall 8-13/16-inch apron.
- Self-Trimming apron overlaps the cabinet face for easy installation.
- No faucet holes.
- Basin slopes 2 degrees toward drain to minimize water pooling.
- Offset drain increases workspace in the sink and storage space underneath.
- Includes cutout templates.

### Material

KOHLER® enameled cast iron.

### Installation

Under-mount apron-front.

### **Recommended Products/Accessories**

K-9000 P-Trap

K-6638 Sink Rack

K-6377 Sponge Caddy

K-6378 Kitchen Brush Caddy

K-6379 Kitchen Squeegee

K-6382 Disinfecting Wipes Dispenser

K-6383 Soap Dispenser

K-8618 Paper Towel Holder

K-8619 Flexible Kitchen Mat

K-8624 Dish Scraper

K-8801 Sink Strainer

K-8799 Sink Strainer



### Codes/Standards

ASME A112.19.1/CSA B45.2

## **KOHLER® Enameled Cast Iron Kitchen Sink Lifetime Limited Warranty**

See website for detailed warranty information.

### Available Colors/Finishes

Color tiles intended for reference only.


Color	Code	Description
	0	White
	FF	Sea Salt™
	96	Biscuit
	47	Almond
	FD	Cane Sugar™
	NY	Dune
	95	Ice™ Grey
	G9	Sandbar
	33	Mexican Sand™
	K4	Cashmere
	FT	Basalt
	58	Thunder™ Grey
	20	Suede
	KA	Black 'n Tan
200	FP	Caviar
	7	Black Black™









# Under-Mount Apron-Front Kitchen Sink K-6487







### **Technical Information**

All product dimensions are nominal.

Bowl configuration: Single

Installation: Under-mount Min. base cabinet 30" (762 mm)

width:

Bowl area (Only): Length: 24-3/4" (629 mm)

Width: 18-1/16" (459 mm) Bowl depth: 9" (229 mm)

Drain hole: 3-5/8" (92 mm)

Template: 1156909-7, required, included

1157000, required, included

#### **Notes**

Install this product according to the installation instructions.

IMPORTANT! The distance from the top edge of the cabinet to the top of the cabinet door must be at least 9" (229 mm) to install this sink.

NOTICE: Countertop manufacturer or cutter must use the cutout template provided with the product, or a current one provided by Kohler Co. (call 1-800-4-KOHLER). Kohler Co. is not responsible for cutout errors when the incorrect cutout

template is used.

